

Screen Colour Systems

Technical Data Sheet

AQ 1001 Aquarius Screen Prep

Description

AQ 1001 - Aquarius Screen Prep is a ready to use gelled solution to degrease and abrade all types of new meshes, prior to the application of Capillary or Indirect Film materials. Use this product to roughen up new meshes only. This product is not recommended for use with direct coated emulsions. Continuous use as this will product will eventually degrade the mesh. See AQ 1003 TDS for all your every day screen preparation requirements.

Technical Info

Low viscosity
Non hazardous
Emulsifiable with water

Application

AQ 1001 should be applied to a wet screen with a soft brush or sponge. Rub the solution into both sides of the mesh and leave for 5 minutes. Wash off with copious amounts of water, preferably with a high-pressure washer until the mesh is free of foam. All excess water should be removed with a vacuum and then allowed to fully dry. Once the screen is dry, the mesh is then ready to receive a new stencil. The screen should be stenciled within twenty four hours of the preparation.

Storage

Prevent from freezing. This products is non-hazardous and non-flammable and as such requires no special storage conditions.

Standard Packaging

AQ 1001 - Aquarius Screen Prep is supplied in 1 litre & 5 litre plastic buckets.

This information is given in good faith but without guarantee. It remains the printer's responsibility to test each product for suitability under their own unique conditions. Screen Colour Systems has a policy of continuous development which may make this information out of date, in the event of any doubt customers are urged to contact the Screen Colour Systems Technical Service Department.